

(LED) LED Power

Output Power	Series	Picture	Circuit	I/P Voltage Range (V.AC)	Output Voltage Range (V.DC)	Isolation Voltage (V.AC)	Operating Temperature	Dimension (mm)	Page
16W	PLF16		Class II	90~264	Single	4000	-30°C~70°C	88.0 x 43.0 x 28.0	54
			Single Stage						
25W	PLF25		Class II	90~264	Single	4000	-30°C~70°C	88.0 x 43.0 x 28.0	54
			Single Stage						
30W	ZQF30 ZQF30(R)		Class I	90~264	Single	3750	-30°C~70°C	101.6 x 50.8 x 28.5	62
			Single Stage						
30W	PLF30		Class II	90~264	Single	3750	-30°C~70°C	125.0 x 60.0 x 35.0	54
			Single Stage						
60W	ZQF60 ZQF60(R)		Class I	90~264	Single	3750	-30°C~70°C	101.6 x 50.8 x 28.5	62
			Single Stage						
	ZLF60		Class I	90~295	Single	3750	-30°C~70°C	104.7 x 52.6 x 27.0	60
			Single Stage						
	AQN60C		Class I	90~305	Single	3750	-40°C~70°C	106.0 x 52.0 x 27.0	52
			Two Stage						
	QLF60		Class I	90~295	Single	3750	-30°C~70°C	120.9 x 60.0 x 35.0	58
			Single Stage						
ALF60		Class I	90~305	Single	3750	-40°C~70°C	120.9 x 60.0 x 35.0	48	
		Two Stage							
PSF60		Class II	90~295	Single	3750	-30°C~70°C	144.0 x 70.0 x 37.5	56	
		Single Stage							
PLF60		Class II	90~264	Single	3750	-30°C~70°C	125.0 x 60.0 x 35.0	54	
		Single Stage							
75W	ZLF75		Class I	90~295	Single	3750	-30°C~70°C	104.7 x 52.6 x 27.0	60
			Single Stage						
	QLF75		Class I	90~295	Single	3750	-30°C~70°C	120.9 x 60.0 x 35.0	58
Single Stage									
PSF75		Class II	90~295	Single	3750	-30°C~70°C	144.0 x 70.0 x 37.5	56	
		Single Stage							
80W	AQN80C		Class I	90~305	Single	3750	-40°C~70°C	106.0 x 52.0 x 27.0	52
			Two Stage						
80W	ALF80		Class I	90~305	Single	3750	-40°C~70°C	120.9 x 60.0 x 35.0	48
			Two Stage						
100W	ZLF100		Class I	90~295	Single	3750	-30°C~70°C	104.7 x 52.6 x 27.0	60
			Single Stage						
	QLF100		Class I	90~295	Single	3750	-30°C~70°C	120.9 x 60.0 x 35.0	58
			Single Stage						
	ALF100		Class I	90~305	Single	3750	-30°C~70°C	163.7 x 71.0 x 38.0	48
Two Stage									
PSF100		Class II	90~295	Single	3750	-30°C~70°C	144.0 x 70.0 x 37.5	56	
		Single Stage							
APF100		Class II	90~305	Single	3750	-30°C~70°C	144.0 x 70.0 x 37.5	50	
		Two Stage							
150W	ALF150		Class II	90~305	Single	3750	-30°C~70°C	163.7 x 71.0 x 38.0	48
			Two Stage						
150W	APF150		Class II	90~305	Single	3750	-30°C~70°C	144.0 x 70.0 x 37.5	50
			Two Stage						
240W	ALF240		Class I	90~264	Single	3000	-25°C~70°C	212.7 x 70.0 x 38.0	48
			Two Stage						