




 AC-DC Switching Power Supply

Output Power	Series	Picture	Package Style	Circuit	I/P Voltage Range (V.AC)	Output Voltage Range (V.DC)	Isolation Voltage (V.AC)	Operating Temperature	Dimension (mm)	Page
60W	AES600		Open Frame	Class I	90~264	5、9、12、15、24、48	3000	-40°C~70°C	103.9 x 52.1 x 25.4 Safety: RoHS CE 	28
	AES60U		U Bracket	Class I	90~264	5、9、12、15、24、48	3000	-40°C~70°C	105.0 x 58.0 x 38.1 Safety: RoHS CE 	28
	AES60E		Enclosed	Class I	90~264	5、9、12、15、24、48	3000	-40°C~70°C	105.0 x 58.0 x 38.1 Safety: RoHS CE 	28
	SZA60 NEW		Open Frame	Class I	90~264	5、12、15、24、48	3000	-30°C~70°C	76.3 x 50.6 x 32.0 Safety: RoHS CE  (Pending)	30
100W	AQF100C (CC Mode)		Open Frame	Class II	90~264	12、15、24、48	3000	-25°C~70°C	103.9 x 52.1 x 25.0 Safety: RoHS CE	32
	AQF100O (CV Mode)		Open Frame	Class II	90~264	12、15、24、48	3000	-25°C~70°C	103.9 x 52.1 x 25.0 Safety: RoHS CE  CB	33
	SZA100 NEW		Open Frame	Class I	90~264	5、12、15、24、48	3000	-30°C~70°C	101.6 x 50.8 x 30.5 Safety: RoHS CE  (Pending)	31
120W	AQF120O		Open Frame	Class I	90~264	5、12、15、24、48	4000	-25°C~70°C	127.0 x 76.2 x 29.5 Safety: RoHS CE  CB	34
	AQF120U		U Bracket	Class I	90~264	5、12、15、24、48	4000	-25°C~70°C	127.0 x 82.2 x 38.1 Safety: RoHS CE  CB	34
	AQF120E		Enclosed	Class I	90~264	5、12、15、24、48	4000	-25°C~70°C	127.0 x 82.2 x 38.1 Safety: RoHS CE  CB	34
160W	AQF160 NEW		Open Frame	Class II	90~264	12、15、24、48	3000	-25°C~70°C	103.9 x 52.1 x 25.0 Safety: RoHS CE  CB	40
240W	AQF240U		U Bracket	Class I	90~264	5、12、15、24、28、32、48	4000	-10°C~70°C	150.0 x 106.0 x 35.0 Safety: RoHS CE  CB	36
	AQF240E		Enclosed	Class I	90~264	12、15、24、28、32、48	4000	-10°C~70°C	150.0 x 106.0 x 35.0 Safety: RoHS CE  CB	36
360W	AQF360U		U Bracket	Class I	90~264	12、24、36、48、54	3000	-10°C~70°C	172.7 x 81.3 x 38.0 Safety: RoHS CE  CB	38
	AQF360E		Enclosed	Class I	90~264	12、24、36、48、54	3000	-10°C~70°C	172.7 x 81.3 x 53.3 Safety: RoHS CE  CB	38
	AQF360F		Enclosed	Class I	90~264	12、24、36、48、54	3000	-10°C~70°C	197.7 x 81.3 x 40.0 Safety: RoHS CE  CB	38
365W	AQF365 NEW		Open Frame	Class I	90~264	12、24、48	3000	-25°C~70°C	127.0 x 76.2 x 32.5 Safety: RoHS CE  (Pending)	41
480W	AQFC480U (CC Mode)		U Bracket	Class I	90~264	12、24、36、48	3000	-20°C~70°C	177.8 x 106.5 x 45.0 Safety: RoHS CE  CB	42
	AQFC480E (CC Mode)		Enclosed	Class I	90~264	12、24、36、48	3000	-20°C~70°C	177.8 x 106.5 x 60.3 Safety: RoHS CE  CB	42
	AQFC480F (CC Mode)		Enclosed	Class I	90~264	12、24、36、48	3000	-20°C~70°C	202.8 x 106.5 x 45.0 Safety: RoHS CE  CB	42
	AQFV480U (CV Mode)		U Bracket	Class I	90~264	12、24、36、48	3000	-20°C~70°C	177.8 x 106.5 x 45.0 Safety: RoHS CE  CB	44
	AQFV480E (CV Mode)		Enclosed	Class I	90~264	12、24、36、48	3000	-20°C~70°C	177.8 x 106.5 x 60.3 Safety: RoHS CE  CB	44
	AQFV480F (CV Mode)		Enclosed	Class I	90~264	12、24、36、48	3000	-20°C~70°C	202.8 x 106.5 x 45.0 Safety: RoHS CE  CB	44
600W	AQF600		Open Frame	Class I	90~264	12、24、48、54	3000	-25°C~65°C	228.5 x 106.5 x 44.0 Safety: RoHS CE  CB	46

AC-DC Power Module

Output Power	Series	Picture	Circuit	I/P Voltage Range (V.AC)	Output Voltage Range (V.DC)	Isolation Voltage (V.AC)	Operating Temperature	Dimension (mm)	Page
2W	AZC NEW		Class II	90~305	Single 3.3、5、9、12、15、24	3000	-40°C~80°C	28.0 x 23.37 x 13.97 Safety: RoHS  (Pending)	08
3W	AIC		Class II	90~264	Single 3.3、5、9、12、15、24	3750	-40°C~85°C	35.7 x 19.0 x 22.0 Safety: RoHS 	09
4W	AOC		Class II	90~264	Single 3.3、5、8、9、12、14、15、24 Dual 5/3.3、8/5、12/5	3000	-40°C~70°C	36.66 x 27.16 x 17.1 Safety: RoHS 	10
	AOCH		Class II	90~305	Single 3.3、5、8、9、12、14、15、24 Dual 5/3.3、8/5、12/5	3000	-40°C~70°C	36.66 x 27.16 x 17.1 Safety: RoHS 	10
5W	AHC		Class II	90~264	Single 3.3、5、12、15、24	3000	-25°C~70°C or -40°C~70°C	50.8 x 25.4 x 15.16 Safety: RoHS 	11
8W	ALC		Class II	90~264	Single 3.3、5、8、9、12、14、15、24 Dual 5/3.3、8/5、12/5	3000	-40°C~70°C	37.5 x 28.0 x 27.4 Safety: RoHS 	12
	AHC08		Class II	90~305	Single 3.3、3.8、5、8、9、12、14、15、24 Dual 5/3.3、8/5、12/5	3000	-40°C~70°C	52.5 x 26.8 x 19.0 Safety: RoHS 	11
10W	AFC		Class II	90~264	Single 3.3、5、12、15、24	3000	-25°C~70°C or -40°C~70°C	52.4 x 27.2 x 23.5 Safety: RoHS 	13
15W	APCN NEW		Class II	90~264	Single 5、12、15、24	4000	-40°C~70°C	55.0 x 45.0 x 20.5 Safety: RoHS 	14
	ATCN NEW		Class II	90~264	Single 5、12、15、24	4000	-40°C~70°C	64.0 x 45.0 x 21.5 Safety: RoHS 	15
	ANCN NEW		Class II	90~264	Single 5、12、15、24	4000	-40°C~70°C	74.0 x 54.0 x 22.0 Safety: RoHS 	16
20W	AFC20		Class II	90~264	Single 3.3、5、12、15、24	3000	-40°C~70°C	52.4 x 27.2 x 23.5 Safety: RoHS 	13
	AKC		Class I	90~264	Single 3.3、5、7.35、9、12、15、24 Dual ± 5 、 ± 12 、 ± 15 Triple 5/ ± 12 、5/ ± 15	3000	-25°C~70°C	70.0 x 48.0 x 22.0 Safety: RoHS 	17
30W	ATC30		Class II	90~305	Single 3.3、5、12、15、24	3000	-40°C~70°C	64.0 x 45.0 x 23.5 Safety: RoHS 	18
	ASC		Class II	90~264	Single 3.3、5、12、15、24 Dual ± 5 、 ± 12 、 ± 15 、5/12 Triple 5/ ± 12 、5/ ± 15	3000	-40°C~70°C	89.0 x 63.5 x 25.0 Safety: RoHS 	19
40W	AJC		Class II	90~264	Single 3.3、5、9、12、15、24 Dual ± 5 、 ± 12 、 ± 15 、5/12、5/24 Triple 5/ ± 12 、5/ ± 15	3000	-40°C~70°C	89.0 x 63.5 x 25.0 Safety: RoHS 	20
50W	ANC50		Class II	90~264	Single 5、12、15、24、48	3000	-25°C~70°C	74.0 x 54.0 x 22.0 Safety: RoHS 	21
60W	AEC60		Class I	90~264	Single 5、9、12、15、24、48	4000	-40°C~70°C	109.0 x 58.5 x 30.0 Safety: RoHS 	22
100W	AQC100		Class I	90~264	Single 12、15、24、48	3000	-25°C~70°C	109.0 x 58.5 x 30.0 Safety: RoHS 	23
125W	AQC125 NEW		Class I	90~264	Single 12、15、24、48	3000	-25°C~70°C	109.0 x 58.5 x 36.0 Safety: RoHS  (Pending)	24

AC-DC Medical Power Module

Output Power	Series	Picture	Circuit	I/P Voltage Range (V.AC)	Output Voltage Range (V.DC)	Isolation Voltage (V.AC)	Operating Temperature	Dimension (mm)	Page
15W	MTC		Class II	90~264	Single 3.3、5、7.35、9、12、15、24	4000	-25°C~70°C or -40°C~70°C	64.0 x 45.6 x 23.5 Safety: RoHS	26
					Dual ± 5 、 ± 12 、 ± 15				
					Triple 5/ ± 12 、5/ ± 15				
40W	MSC		Class II	90~264	Single 3.3、5、9、12、15、24	4000	-25°C~70°C or -40°C~70°C	89.0 x 63.5 x 27.0 Safety: RoHS	27
					Dual ± 5 、 ± 12 、 ± 15				
					Triple 5/12、5/24				

ANSI/AAMI ES 60601-1: 2005, 1st Edition and CAN/CSA-C22.2 No. 60601-1:08, 2nd Edition, MOPP